

ADHESIVE TAPE OPTION

# 3M VHB (Very High Bond) tape #5925

See other installation options using Silicone or Instant Adhesive

We do not offer our safety padding with PSA (Pressure Sensitive or Peel/Stick Backing).

## VHB Tape Solution - For installation where silicone is not an option

- This is the "only" tape we found that will stick to both our products and most other surfaces
- Tape needs 72 hours to set for maximum adhesion
- Tape is expensive relative to silicone
- We do not attach the tape for you
- We cannot cut the tape and re-spool into smaller rolls

### **Tape Properties**

Single sided foam tape Color: Dark Grey or Black Width: 1" or 1/2" Thickness: .06" (25 mil)





# Instructions:

1. Clean surfaces with mineral spirits or similar product to help adhesion

- 2. Peel& Stick
- 3. Wait for it to bond properly IMPORTANT bonding strength develops over time
  - 20 minutes = 50% of ultimate strength
  - 60 minutes = 75% of ultimate strength
  - 24 hours = 90% of ultimate strength
  - 72 hours = 100% of ultimate strength

Sorry, we do not sell this tape as customers can purchase directly Available at: - Local 3M dealers

- U-Line (http://www.uline.com/BL\_6052/3M-5925-VHB-Acrylic-Foam-Tape)

Average retail price: <sup>1</sup>/<sub>2</sub>" = \$96.00 / 72 yd roll (= 216 ft = 2,592") 1" = \$159.00 / 72 yd roll (= 216 ft = 2,592")

# Silicone Solution - For most applications

- Silicone provides heavy duty adhesion
- With silicone, you can add a bead around the outer edge to seal off from dirt/liquids/tampering
- Silicone will adhere to virtually any surface including rough textures like brick

#### Instant Adhesive Solution - For many applications

- Instant Adhesive is like "Superglue"
- Great for very strong/permanent bonding
- Best for applying to smooth surfaces

#### **Velcro Solution** - *For removable applications*

- Best for applications where you need to periodically remove and re-attach the padding
- Requires you to attach the Velcro to the padding with instant adhesive

#### Boing product warranty is voided if non-approved adhesive is used

Effective 1 January 2012

Network USA Inc. Companies 136 Walker Street, Atlanta GA 30313 TEL 404-521-9054 ORDER: 800-477-6434 FAX: 404-222-8366 wwwBoingSafety.com info@BoingSafety.com